



Zipcord 200 μ m 2.5 mm LSZH HCS® Fiber Optic Cable

P/N: C21051

Overview	Designed specifically for indoor use, these simplex and zipcord designs with 2.25 mm outer jackets are constructed with low smoke zero halogen (LSZH) cable materials from HCS fibers. They are appropriate for indoor riser installations in enclosed or sealed locations. These cables are crimp and cleave compatible with ST or SMA connectors. LSZH materials also offer a higher operating temperature range than comparable HCS cables.
Typical Applications	• Nuclear Power Plants • Offshore Marine Platforms • Shipboard Systems

Product Specifications	
Product Description	Zipcord 200 μm 2.5 mm LSZH HCS Fiber Optic Cable
Physical Characteristics	
Construction	Zipcord
Fiber Core Diameter	200 $\pm$ 4 μ m
Sub-Unit Diameter	2.5 $\pm$ 0.2 mm
Outer Cable Diameter	2.5 x 5.2 mm
Cable Weight	< 14.0 kg/km
Outer Jacket Material	LSZH
Outer Jacket Color	Orange
Specialty Testing (IEC 754-2 Acid Gas - Halogen Content)	Passes
Specialty Testing (IEC 332-3 Flammability Rating)	Passes
Specialty Testing (Cyclic Flexing)	> 50,000 Cycles
Crimp & Cleave Compatibility	SMA and ST Connectors
Optical Characteristics	
Type	Multimode Step-Index
Attenuation @ 850 nm	$\leq$ 6 dB/km
Mechanical and Environmental	
Installation Load (Maximum)	165 lb. (734 N)
Operating Load (Maximum)	85 lb. (378 N)
Minimum Bend Installation	38 mm
Minimum Bend Operating	25 mm
Operating Temperature	-20 to +80 $^{\circ}$ C
Storage Temperature	-40 to +80 $^{\circ}$ C
Intended Location	Indoor
Order by Part Number	C21051
Product Description Code	HCP-M0200T-A02ZZ
OPTIONS	Also available in breakout construction with up to 18 sub-units, jacket color, outer jacket material, print legend, terminated assemblies
NOTE	The operating temperature ranges are general guidelines. Consult with our Technical Sales department to determine the optimal coating and jacketing material for your specific application. 1.860.678.6636.
Contact Information	For additional information please contact your sales representative. You can also visit our website at www.lightera.com or call 1-888-FIBERHELP (1-888-342-3743) USA or 1-770-798-5555 outside the USA. For a full list of our certifications, visit our website.
Trademark Notice and Disclaimer	Lightera reserves the right to make changes to the product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any Lightera warranties or specifications relating to any of its products or services.