



50/125 Launch Optical Fiber

P/N: BF06864

Product Overview

These multimode step-index launch optical fibers are designed with low 0.22 numerical aperture — an extra low 0.15 NA is also available. These configurations can handle peak power delivery approaching 1GW/cm². The coating offers easy mechanical stripping and is compatible with either carbon or PYROCOAT® polyimide coatings, or both, when various combinations of hermeticity and/or high temperature resistance are needed. Launch fibers can also be metalized for hermetic sealing into opto-electronic devices.

Typical Applications

- Diode Pumping Systems
- Free Space Optics
- Medical Sensing and Imaging
- Other Industrial Applications
- Power Transmission from Visible through Near-IR
- Printing
- Raman Pumping
- SM and MM Communications
- Use as Input Fiber in a Power Combiner

Product Specifications	
Product Description	50/125 Launch Optical Fiber
Physical Characteristics	
Core Diameter	50 ± 3.0 µm
Cladding Diameter	125 ± 2.0 µm
Coating Diameter	250 ± 15 µm
Core/Clad Offset	≤ 3 µm
Coating Concentricity	≥ 80%
Clad Non-Circularity	≤ 2.0%
Crimp & Cleave Compatible	No
Coating Material	Dual UV Acrylate
Optical Characteristics	
Type	Multimode Step-Index
Numerical Aperture	0.22
Numerical Aperture Tolerance	± 0.02
Attenuation @ 850 nm	≤ 5 dB/km
Water Content	Low OH
Mechanical and Environmental	
Operating Temperature	-40 to +85 °C
Short-Term Bend Radius	≥ 10 mm
Long-Term Bend Radius	≥ 17 mm
Proof Test Level	≥ 100 kpsi (0.689 GPa)
Order by Part Number	BF06864
OPTIONS	Buffering, Cabling, Coating Color, Connectorization, Core Diameter, Metalization
Contact Information	For additional information please contact your sales representative. You can also visit our website at www.lightera.com or call 1-888-FIBERHELP (1-888-342-3743) USA or 1-770-798-5555 outside the USA. For a full list of our certifications, visit our website.
Trademark Notice and Disclaimer	Lightera reserves the right to make changes to the product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any Lightera warranties or specifications relating to any of its products or services.