



Coreless Termination Optical Fiber - Acrylate Coated

P/N: F15330

Product Overview

Termination optical fiber is a coreless silica fiber. It is useful for eliminating back reflections from unused branches of a multi-port device as well as performing return loss measurement.

A termination of better than 65 dB is achieved by splicing approximately 0.25 meters of this fiber to the desired component. A fusion splice also provides higher reliability and long-term stability over conventional termination methods.

There is excellent repeatability since there is no potential for subsurface damage, fiber breakage, or fiber contamination as with polished or angled cleaves. A quality termination using a patented method (U.S. Patent No. 5,263,103) is possible for all fiber designs including high delta fibers such as erbium-doped fiber.

Product Specifications

Product Description Coreless Termination Optical Fiber - Acrylate Coated

Physical Characteristics

Coating Material Dual UV Acrylate

Glass Diameter $125 \pm 1 \mu\text{m}$

Coating Diameter $250 \pm 10 \mu\text{m}$

Core Non-Circularity $< 2\%$

Coating Concentricity Error $\leq 6 \mu\text{m}$

Mechanical and Environmental

Operating Temperature -40 to $+85 \text{ }^{\circ}\text{C}$

Proof Test Level 200 kpsi (1.38 GPa)

Order by Part Number **F15330**

Contact Information

For additional information please contact your sales representative. You can also visit our website at www.lightera.com or call 1-888-FIBERHELP (1-888-342-3743) USA or 1-770-798-5555 outside the USA. For a full list of our certifications, visit our website.

Trademark Notice and Disclaimer

Lightera reserves the right to make changes to the product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any Lightera warranties or specifications relating to any of its products or services.