



365-22 HCXtreme® Optical Fiber

P/N: F18940

Product Overview

The Lightera family of High-Power Delivery optical fibers includes the HCXtreme product line. HCXtreme fibers are low-OH, all-silica fibers coated with HCS® fluoroacrylate to improve fiber strength and to improve resistance to fatigue. A blue ETFE is applied as the standard outer buffer on these step-index, multimode fibers, indicating the primary use for medical applications. The 365-22 HCXtreme Optical Fiber offers a nominal NA of 0.22. These fibers are also available in other core sizes and core/clad ratios. HCXtreme fibers are made with biocompatible materials. HCXtreme Optical Fiber coating technology solves the problem of fiber failure due to excessive bending of optical fiber under power. In testing down to 2.5 mm radius bend, HCXtreme fibers continued to transmit power without breakage. Actual performance in any given application should be validated by customer testing. For further details and testing methodology, request our white paper, entitled “Study of Optical Fiber Damage Under Tight Bend with High Optical Power at 2140 nm.”

Typical Applications

- Cascaded Laser Power Delivery
- High-Power Laser Delivery
- Industrial Cabling
- Laser Surgery
- Laser Welding and Cutting
- Near-IR (up to 2100 nm)
- Laser Power Delivery

Product Specifications	
Product Description	365-22 HC X
Physical Characteristics	
Core Diameter	365 ± 10 µm
Cladding Diameter	400 ± 10 µm
Hard Coating Diameter	430 ± 10 µm
Buffer Diameter	550 ± 30 µm
Clad/Coating Offset	≤ 9 µm
Crimp & Cleave Compatible	Yes
Buffer Material	ETFE
Standard Buffer Color	Blue
Coating Material	HCS®
Optical Characteristics	
Type	Multimode Step-Index
Numerical Aperture	0.22
Attenuation @ 850 nm	≤ 10 dB/km
Water Content	Low OH
Mechanical and Environmental	
Operating Temperature	-65 to +125 °C
Short-Term Bend Radius	≥ 29 mm
Long-Term Bend Radius	≥ 47 mm
Proof Test Level	≥ 100 kpsi (0.689 GPa)
Order by Part Number	F18940
Product Description Code	365-22 HCxtreme
Contact Information	For additional information please contact your sales representative. You can also visit our website at www.lightera.com or call 1-888-FIBERHELP (1-888-342-3743) USA or 1-770-798-5555 outside the USA. For a full list of our certifications, visit our website.
Trademark Notice and Disclaimer	Lightera reserves the right to make changes to the product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any Lightera warranties or specifications relating to any of its products or services.