





**LIGHT MEASUREMENT
MADE EASY**



DESIGN YOUR OWN TEST LAB WITH SCANDINAVIAN EXPERTISE

From Copenhagen, Denmark, we will support you in designing and creating a productive light measurement lab. Our customers span from general, architectural, horticultural, and automotive lighting to UV lighting and more.



All businesses can take advantage of the latest lighting technology by having their own productive test lab - even small and medium-sized.

The constant evolution of LED products creates a demand for a lot of measurements. Clients expect much more detailed product specifications and new regulations require more in-house expertise.

Viso light measurement systems are designed to meet the demands of all company sizes.

VISO SYSTEMS

Since 2006, Viso Systems has been at the forefront of developing and manufacturing some of the most innovative light measurement solutions in the world.

We have eliminated the need for an integrating sphere and replaced it with a single system that measures both light distributions (IES files) and color metrics in one go.

We have simplified the complexity of light measurement by providing smart and user-friendly software.

DESIGN

We develop and improve our products every day—often in interaction with our customers. Your input and ideas are important to us. Close dialogue with users and authorities ensures that our systems are always suitable for your tasks and meet new requirements.

Viso Systems equipment is suitable for many different applications, such as general lighting, horticulture, and LED components. We help our clients customize equipment, installations, and reports to suit specific needs.

PRODUCTION

All production and development take place at Viso Systems' headquarters and within our network of experienced suppliers.

Our products are assembled, meticulously tested, and certified before shipment. The delivery time is usually only 2-3 weeks.



TWO MEASUREMENT SOLUTIONS



LabSpion

For any light sources **up to 45 kg** (100 lbs). Spectrometer sensor with built-in laser distance detector on a tripod.



BaseSpion

For medium-sized light sources **up to 9 kg** (20 lbs). Spectrometer sensor slides on a tabletop rail.

ONE SOFTWARE FOR ALL

The Viso Light Inspector software is the most intuitive light measurement software solution on the market.

The software provides you with a perfect overview of all your measurement data in real-time. We know that fast measurements with smart data processing are crucial for your business.

Export IES/LDT/XML files and create fully customized reports in PDF and Excel.


We offer frequent updates based on customers' needs.

ACCESSORIES

The extensive Viso accessory range provides everything you need for your photometry lab. It includes temperature measurements, DALI/DMX control, and advanced power supplies. With Viso systems and accessories, you can get everything you need for your lab in one place.

Light Inspector

The software works with all Viso products and makes measurements easy.



The LabSpion® gives you the capability to measure the full range of lamps, from small LED chips to very large panels and streetlights up to 45 kg (100 lbs).

The fast spectrometer sensor and a built-in power analyzer give you fast and comprehensive measurements and ensure that all data are measured quickly, making other types of equipment, such as integration spheres, redundant.

MEASURE IN 30 SECONDS AND GET:


- Full IES and LDT files
- Lumen
- Peak candela value
- Color temperature, CCT
- Spectrum, CRI, TM30, CQS
- Beam angle
- Detailed angular field distribution
- Power and power factor
- Lumen per watt
- Radiometrical units
- Horticultural units
- ... and much more



The 2-axis goniometer gives you the full 3D light distribution



Just plug in the USB cable and everything is fully integrated




High-speed spectrometer sensor ensures fast and reliable measurements



The distance is easily measured with the integrated laser

EASY CONNECTIVITY



LABSPION SPECIFICATIONS

Measurement method	Far field, type C horizontal
Spectrometer ranges	VIS (standard) 360 – 830 nm
	Also available in:
	UV-VIS 200 – 830 nm
	UV-VIS-NIR 200 – 1100 nm
	VIS-NIR 360 – 1100 nm<
Sensor distance range	70 cm → 25 m (2.3 ft → 80 ft)
Sensor distance setup	Manual, built-in laser distance sensor
Lamp diameter range	0 – 1.5/2.0 m (4.9 / 6.6 ft)
Lamp maximum weight	25 kg / 45 kg (55 lbs / 99 lbs)
Power supply input	90 to 260 VAC, 50/60 Hz

More specifications on page 24 – 25

BASESPION

The BaseSpion® is the perfect solution for any mid-size laboratory that wants to perform advanced light measurements with a compact system. The best solution for testing LED chips, modules, panels, downlights, bulbs, and spotlights up to 9 kg (20 lbs).

The BaseSpion is a great tool that allows you to measure all medium-sized lighting products. The 2-axis goniometer enables the system to measure full 3D distribution fields of any light source and gives lighting professionals comprehensive IES and LDT simulation files



COMPACT

The BaseSpion is a professional laboratory tabletop light measurement system. It offers fully automated multiple C-plane measurements. The design of the system makes it very flexible to work with in any lighting laboratory. The goniometer drivers and power analyzer are all built-in. Simply connect via USB to any PC and get results in just 30 seconds.


BASESPION SPECIFICATIONS

Measurement method	Far field, type C horizontal
Spectrometer range	VIS (standard) 360 – 830 nm Also available in: UV-VIS 200 – 830 nm UV-VIS-NIR 200 – 1100 nm VIS-NIR 360 – 1100 nm
Sensor distance range	35 cm to 450 cm (14" – 14.7 ft)
Sensor distance setup	Automatic detector on rail
Lamp diameter range	0 – 54 cm (0 – 21.5")
Lamp maximum weight	9 kg (19.8 lbs)
Power supply input	90 to 260 VAC, 50/60 Hz

More specifications on page 26 – 27

MEASURE IN 30 SECONDS AND GET:

- Full IES and LDT files
- Lumen
- Peak candela value
- Color temperature, CCT
- Spectrum, CRI, TM30, CQS
- Beam angle
- Detailed angular field distribution
- Power and power factor
- Lumen per watt
- Radiometrical units
- Horticultural units
- ... and much more



The universal light source bracket easily clicks onto the goniometer



Before measurement, simply slide, align and lock the light source to the center



The base lock makes it easy to align the light source with sensor




The automatic sensor positioning system ensures fast and accurate distance setup




LIGHT INSPECTOR SOFTWARE

The Viso Light Inspector® is the most intuitive goniometer interface and software system on the market. It is included with all Viso light measurement products. All measured data is shown in real time. Photometric results are displayed graphically to give you a fast overview.




PACKED WITH FEATURES


- User-friendly graphical interface
- Automatic goniometer setup
- Graphical power analyzer
- Real-time measurement data view
- Detailed angular distribution
- Add product image and description
- Make your own measurement templates
- Fully **customized pdf reports** with your design
- IES/LDT and lots of special exports (XLS, XML, GLDF)
- Direct export to **ready-to-upload EPREL zip files**
- Connect directly to MATLAB , LabVIEW, etc.
- Compatible with Windows 7, 8, 10 and 11




One click starts the fully automatic setup and measurement cycle



Comprehensive color quality data results, including CRI, CQS and TM30 values



Real power efficiency can be calculated using the radiated spectral energy



Easily add light sources dimensions. Rotate, symmetrize and correct.

THE SOFTWARE


The software gives you a great real-time overview of measurements. The user-friendly functions of the software allow you to get fast results and will help you analyze and report every detail.

The software supports various measurement styles:


- Photometric units (light for human vision)
- Radiometric units (UV and infrared)
- Horticultural units (green house lighting)
- Dose units (for UV exposure)

EXPORT

PDF



LDT
IES



EXCEL
XML
CSV



REPORT DESIGNER

Design your report templates for your own company style. No need to copy-paste or ask any other department to customize your reports for a unique look. Use Viso's Report Designer to export directly to the client or to your website in the format you desire.

VISO
SYSTEMS







LOTS OF EXPORT OPTIONS

Light Inspector allows you to make several kinds of outputs - scientific and for marketing:


- Light distribution files in IES and LDT formats as well as TM33 and TM27 XML outputs.
- Raw data as .csv or MS Excel spreadsheets
- PDF standard reports
- EU: Direct export to EPREL zip file - ready to upload to the EPREL database
- Customized reports based on your own templates.
The Light Inspector allows you to design your own PDF report templates using Microsoft Office Word as an editor. Everything you can design in MS Word, you may include - even embedded MS Excel spreadsheets aWwNd custom graphics and logos

EXPORT TO


PDF REPORT DESIGNER




Simply add, move and/or resize any photometric graphic (vector graphics)










Extensive library of graphics with any photometric data. Just drag and drop into your report



Use keywords to place photometric values anywhere and create tables



Unlimited number of PDF templates can be saved and selected with preview




LabFlicker

LabFlicker® is the first flicker measurement instrument to integrate seamlessly with your light measurement system. Complete your photometric reports with flicker data.

RESULTS

SVM, PstLM
Percent FlickerW
Flicker index
Flicker frequency
MP (Assist)
JA8/10 (Title 24)




Connects directly to your PC via USB allowing for a fast, real-time preview



OLED display gives live flicker results during measurement



An ultra-fast 350,000 samples/sec photo sensor gives you precise data



Seamless integration with Viso pdf-reporting: All photometrics in one output

LabRail



The unique LabRail® system together with LabSpion goniometer is a complete light measurement solution. Setting the sensor distance has never been easier

LABRAIL PROVIDES PERFECT ALIGNMENT

The LabRail system combines your full-size LabSpion goniometer with a rail-based sensor system.

Rail length 12 m (39.4 ft) is standard—but both shorter and longer rails are available. The rail assembly is suspended from the ceiling in the laboratory.

Sensor movement along the rail is motorized. The sensor distance can be optimized for all-sized light sources. Owners of LabSpion systems may replace the standard tripod arrangement with the LabRail upgrade kit.

GO ANYWHERE IN 5 SECONDS

- Repositioning the sensor in only 5 seconds
- Perfect alignment every time
- No cables
- Free up your floor space
- Automatic positioning
- Suspension from ceiling



The integrated laser measures the distance to the light source automatically

SPECIFICATIONS

Sensor distance range	35 cm (14") to 1200 cm (39.4 ft) (standard)
Sensor distance setup	Automatic
Power supply input	90 to 260 VAC, 50/60 Hz

More specifications in page 25

ORIGINAL VISO ACCESORIES

LabPower

STEADY AC SUPPLY AND POWER DATA

Viso LabPower is a combined AC power supply and power analyzer that complies with light measurements standards (IES LM-79 and CIE S 025).

LabPower is a dedicated AC power supply and power analyzer. It has full integration with any Viso light measurement system. It has a versatile max. 250 W output range 90-270 VAC / 50-60 Hz.

It removes all mains voltage fluctuations throughout the measurement and provides low harmonic distortion and no resonance artifacts using advanced control loops.

LabPower provides real-time readout on the built-in display. Further, it has an optional remote sensing feature for optimal accuracy.

[LINK TO ONLINE PRESENTATION](#)



LabAnalyzer

KEEP TRACK OF YOUR POWER CONSUMPTION

Viso LabAnalyzer is an advanced AC and DC power analyzer that complies with light measurements standards (IES LM-79 and CIE S 025). LabPower fully integrates with your Viso light measurement system and software, and facilitates remote sensing.

LabAnalyzer keeps track of your power consumption in every detail. It is both easy to install and to use, and provides precise power measurements for both AC and DC. The built-in display shows advanced harmonics analysis, power graphics, power factor and displacement factor. Get all results directly into your light measurement file through the USB connection.

It has a versatile measurement range (up to 100 kHz, 2-270V AC/DC, up to around 2000 W), and a sample rate of 2 mega samples per second.

[LINK TO ONLINE PRESENTATION](#)



Sensor upgrades

EXPAND YOUR MEASUREMENT RANGE

BaseSensor and LabSensor model II can both be fitted with detectors that go beyond the visible spectrum - for UV light down to 200 nm, and for near infrared up to 1100 nm. To comply with EPREL, measurements down to 250 nm are needed.

Your existing VIS system (360-830 nm) can be upgraded to:

- LabSensor / BaseSensor UV-VIS (200-850 nm)
- LabSensor / BaseSensor UV-VIS-NIR (200-1100 nm)
- LabSensor / BaseSensor VIS-NIR (360-1100 nm)

All Viso BaseSpion and LabSpion systems contain high-end Ibsen Photonics FREEDOM with custom Viso high sensitive transmission gratings. Viso UV sensors have advanced straylight correction.

[LINK TO ONLINE PRESENTATION](#)



FOR STROBING LIGHT SOURCES

All the same functions as the LabAnalyzer but with a unique feature that allows your Viso light measurement system to measure strobing light sources while they are flashing.

The revolutionary LabAnalyzer with sensor sync synchronizes LabSensors/BaseSensors with measured power pulses. This makes it possible to make accurate 3D measurement of a light source that is continuously flashing. In this way, the light source will be measured as it is used and with a realistic temperature.

The system measures the details of the flash waveform including peak voltage, amps, intensity, period length, number of flashes per period, flash lengths, interval lengths, etc.

[LINK TO ONLINE PRESENTATION](#)



LabDisc


REMOVE STRAYLIGHT

LabDisc is an accessory to Viso LabSpion and BaseSpion light measurement systems. This adjustable baffle reduces straylight errors to a minimum by restricting your sensor’s field of view.

The perfect darkroom does not exist. Although all lab surfaces are black, a small amount of light is always reflected.

This stray light can reach your sensor and interfere with your result. Therefore, it is important to avoid stray light from lab surfaces.

LabDisc removes all stray light from side walls, ceiling and floor and reduces stray light from the rear wall to a minimum.



Stem version for BaseSpion available (magnetic).

[LINK TO ONLINE PRESENTATION](#)

LightInterface

CONTROL YOUR LAMP DURING MEASUREMENT

Many light sources are dimmable or color tunable. LightInterface allows the Light Inspector software to communicate with your device driver using the most common protocols (DMX, DALI, and 0-10 V).

Measure your light source in a specific setting or create a special tuning protocol with several settings using the LightInspector software.

With LightInterface, you can control your light sources throughout your measurement cycle, set up custom measurement protocols, and save all results in a single report. Analyze your results using the customizable software graphics, or export all details.

Plot your dimming and color tuning curves.



LabTemp

RECORD TEMPERATURE THE EASY WAY

Measure and record your device temperature and ambient temperature in your lab. LabTemp is a hub with one internal and three standard external temperature probes. LabTemp connects to Viso LabSpion and BaseSpion.

The LabTemp hub is attached to the goniometer with strong magnets. The internal sensor captures ambient temperature data with any Viso BaseSpion and LabSpion while measuring light. It is easy to install and use. No extra software, no extra power supply and no extra data cables.

The external probes can measure the temperature at specific points of interest.

Ambient temperature verification is mandatory in CIE S 025/E:2015 guidelines.



LabTarget


PERFECT AND FAST ALIGNMENT

LabTarget is a Viso LabSpion and BaseSpion accessory. This vertical, crossbeam laser is mounted on the ceiling above your goniometer and makes it simple to align your light source perfectly with the rotational center.

LabTarget is the first vertical, double-plane laser level on the market. Install the LabTarget above your Viso LabSpion or BaseSpion light measurement systems and make light source alignment easier than ever.

The laser beam is on when your light measurement system is on and turns off automatically during measurements

LabTarget is included with Viso LabRail.



ORIGINAL VISO LIGHT SOURCES

Labarazzi

UNIQUE FLICKER GENERATOR

Labarazzi is a special tunable light source that can generate flicker, i.e. temporal light artifacts. Use Labarazzi to calibrate flicker testers, to test cameras for flicker immunity and for teaching and demonstration.

Viso Systems Labarazzi is the only commercially available TLA generator in the world. Labarazzi is a professional laboratory and demo light source that generates precise temporal light artifacts (TLAs). The Labarazzi has a 1100 lumen LED light source.

The Labarazzi offers 26 preset flicker signals with different waveforms, frequencies, percent flicker, duty cycles, modulation depths, PstLM and SVM. Design custom TLA waveforms with the Light Inspector software.

[LINK TO ONLINE PRESENTATION](#)



CALI-T50

REFERENCE LAMP (VIS/VIS-NIR)

Get your own custom calibration lamp. The CALI-T50 is used with Viso VIS and VIS-NIR sensors (wavelength range 360-1100 nm).

The CALI-T50 is a tungsten irradiance reference lamp with an auto ramp-up power supply. This reference lamp can be used to recalibrate/verify your calibration at any time without the need for external support. It is easily mounted in the center bracket of the LabSpion or BaseSpion. The CALI-T50 is included in LabSpion VIS/VIS-NIR.

All CALI-T50 sources are traceable to PTB 2302 Blackbody radiator - the PTB national primary standard for spectral irradiance calibration lamps.

[LINK TO ONLINE PRESENTATION](#)



REF-800

FAST CALIBRATION CHECKUP

This lamp can be used to regularly verify that your calibration is still good. The set consists of a COB LED on a large heat sink and a dedicated driver. The REF-800 is characterized using your particular sensor in the course of every factory (re)calibration.

This special Viso reference light source (REF-800) is included with all new Viso light measurement systems. Its purpose is to facilitate quick tests of whether the spectrometer properties have drifted, indicating that recalibration is needed. With the REF-800, you may also avoid unnecessary wear on your calibration lamps such as CALI-T50 or CALI-DT300.

[LINK TO ONLINE PRESENTATION](#)



EXTENDS LIGHTSPION RANGE TO 22 cm SOURCES

The briefcase-based Viso LightSpion system is now discontinued. You can still get LightSpion Extender - and all services and support.

The LightSpion Extender is an optional accessory for measuring light sources that exceed 8 cm in diameter. The LightSpion Extender provides you with the distance necessary to measure light sources up to 22 cm (8.7") in diameter and up to 5 kg (8.8 lbs) in weight.

Manual rotation of the lamp in 45-degree steps (up to 8 c-planes) allows measuring of asymmetrical light sources.



Calibration

FAST AND EASY

Calibration every two years

At the heart of every measurement system is ascertaining that results are correct. Viso Systems generally recommends that devices are recalibrated every year or at least every two years.

Do your own calibrations

Viso Systems measurement systems can be recalibrated using original Viso reference light sources, CALI-T50 and CALI-DT30. Alternatively, use a calibration lamp of your own choice. A CALI accessory is included with all LabSpion systems.

Let Viso Systems help with your calibrations

Just send your sensor or your LightSpion to Copenhagen for recalibration. Remember to include original reference lamps. Expect 1-2 weeks lead time + shipping time. Send your service request directly to Viso headquarters (info@visosystems.com) or to your local distributor.



Get an online demo

SHIP YOUR LIGHTING FIXTURE TO VISO AND GET A FREE ONLINE MEASUREMENT DEMONSTRATION

Viso Systems now offers an exclusive opportunity: Potential clients can ship a lighting product of their own and get a demo. We will then run a complete light measurement as an exclusive, live, commented online demonstration including:

- Mounting your luminaire (or Viso demo light source) on a Viso system
- Detailed demo of the setup
- Running a full measurement
- Q&A – ask as many questions as you want
- Collecting the full output in a report + IES/LTD + Excel
- Sending the outputs to you

Before buying, experience just how powerful Viso Software is in practice.

Once you receive the original measurement file from the demo you can open it in the Light Inspector software:

Free download from www.visosystems.com/download-light-inspector/.

Make your own experiments, views and adjustments. Generate reports (IES, PDF, MS Excel, etc.).

Flexible mounting


DETACHABLE LAMP BRACKET


The multifunctional mounting bracket creates endless ways of mounting your luminaire on the LabSpion goniometer system.


The detachable bracket is standard on all new LabSpion light measurement systems. For older systems it is available as an accessory.

The detailed hole pattern provides many possibilities for mounting light sources and fits all LabSpion models.

Detach the entire bracket and take it to the workshop. Quick and easy to attach to the Gonio tower with two sturdy hooks and two large thumb screws.




		LabSpion VIS Standard version	LabSpion UV-VIS
Physical Dimensions		As standard version	
Shipping Weight	90 kg (198 lbs)		
Dimensions (L x W x H)	190 x 190 x 162.5 cm (6.2 x 6.2 x 5.3 ft)		
Weight	78 kg (172 lbs)		
Sensor Distance Range	0.5 to 50 m (1.6 to 160 ft)-		
Sensor Distance	≥ Light Source Length x 10 (Min. x 8)		
Sensor Distance Set-Up	Laser Range Finder, ±2 mm		
Light Source Diameter Range	0 – 1.5 m (0 – 4.92 ft) @ 2-Axis		
Light Source Diameter Range, Tall Tower	0 – 2.0 m (0 – 6.56 ft) (@ 2-Axis		
Light Source (DUT) Maximum Weight	25 kg (55 lbs)		
Light Source (DUT) Maximum Weight, Enforced	45 kg (99 lbs)		
Electrical Specifications		As standard version	
Power Supply Input	90 – 260 VAC, 50/60 Hz		
Power Analyzer Voltage Range	90 – 260 VAC < ±0.5 V		
Power Analyzer Current Range	0 – 3 A (Average ±0.5 mA)		
Power Analyzer Power Range @ 230 V	0 – 600 W (Average: ±0.1 W)		
Power Analyzer Power Range @ 110 V	0 – 300 W (Average: ±0.1W)		
Power Analyzer Sample Rate	70,000 Samples/sec		
Photometric Specifications		As standard version	
Measurement Method	Far-Field	Far-Field	
Illuminance, Lux at Sensor (Equal to cd @ 1 m)	0.20 – 200,000 lux <±2,5%	0.40 – 400,000 <±2,5% lux	
Max intensity @ 1.0 m	0.2 – 200,000 cd <± 2,5%	0.40 – 400,000 cd <± 2,5%	
Max intensity @ 20.0 m	80 – 80,000,000 cd <± 2,5%	160 – 160,000,000 cd <± 2,5%	
Flux Range, Min. Distance (Lambertian Distribution)	0.63 – 630,000 lm @ 1.0 m	Radiated spectral energy In W/nm Irradiance in µW/cm² or W/m² (all directions) 3D UV-VIS radiation field	
Flux Range, Max. Distance (Lambertian Distribution)	250 – 250,000,000 lm @ 20.0 m		
Flux accuracy	VIS ±4 %	VIS ±4%, UVA/B ±5%, UVC ±6.5%	
Color Temperature Range	1,000 K – 10,000 K < ±35 K	1,000 K – 10,000 K < ±35 K	
Color Rendering Index	Up to 100 < ±0.7	Up to 100 < ±0.7	
Resolution, Standard	5 Degrees/Step (Auto-Detect)	5 Degrees/Step (Auto-Detect)	
Resolution, Highest	0.01 Degrees/Step (Auto-Detect)	0.01 Degrees/Step (Auto-Detect)	
Number of c-planes	2 – 72 (max. 144) automatic	2 – 72 (max. 144) automatic	
Spectrometer Type	Ibsen Photonics FREEDOM High Efficiency Transmission Grating	Ibsen Photonics FREEDOM High Efficiency Transmission Grating	
Spectrometer Range	360 – 830 nm (1024 pixels)	200 – 850 nm (2048 pixels)	
Spectrometer Detector	Hamamatsu S11639-01	Hamamatsu S11639-01	
Calibration	Fully Calibrated Plug-and-Play Solution	Fully Calibrated Plug-and-Play Solution	
Re-calibration	Min. Every Two Years	Min. Every Two Years	

LabSpion UV-VIS-NIR	LabSpion VIS-NIR		LabRail for LabSpion
<i>As standard version</i>	<i>As standard version</i>	<i>As standard version</i>	
		35 kg (77 lbs)	
		25 x 25 x 160 cm (0.8 x 0.8 x 5.3 ft)	
		30 kg (66 lbs)	
		0.5 to 12 m (1.6 to 39.4 ft)	
		Standard up to 12 m (39,4 ft) (can be extended)	
		Laser Range Finder, Automatic, ±2 mm	
<i>As standard version</i>	<i>As standard version</i>	<i>As standard version</i>	
		90 – 260 VAC, 50/60 Hz	
<i>As preferred LabSpion version</i>			
Far-Field	Far-Field	Far-Field	Far-Field
0.40 – 400,000 <±2,5% lux	0.40 – 400,000 <±2,5% lux	0.40 – 400,000 <±2,5% lux	0.40 – 400,000 <±2,5% lux
As UV-VIS version	As UV-VIS version	As UV-VIS version	As UV-VIS version
NIR ±4%, VIS ±4%, UVA/B ±5%, UVC ±6.5%	NIR ±4%, VIS ±4%, UVA/B ±5%, UVC ±6.5%	VIS ±4%, NIR ±4%	VIS ±4%, NIR ±4%
1,000 K – 10,000 K < ±35 K	1,000 K – 10,000 K < ±35 K	1,000 K – 10,000 K < ±35 K	1,000 K – 10,000 K < ±35 K
Up to 100 < ±0.7	Up to 100 < ±0.7	Up to 100 < ±0.7	Up to 100 < ±0.7
5 Degrees/Step (Auto-Detect)	5 Degrees/Step (Auto-Detect)	5 Degrees/Step (Auto-Detect)	5 Degrees/Step (Auto-Detect)
0.01 Degrees/Step (Auto-Detect)	0.01 Degrees/Step (Auto-Detect)	0.01 Degrees/Step (Auto-Detect)	0.01 Degrees/Step (Auto-Detect)
2 – 72 (max. 144) automatic	2 – 72 (max. 144) automatic	2 – 72 (max. 144) automatic	2 – 72 (max. 144) automatic
Ibsen Photonics FREEDOM	Ibsen Photonics FREEDOM	Ibsen Photonics FREEDOM	Ibsen Photonics FREEDOM
High Efficiency Transmission Grating	High Efficiency Transmission Grating	High Efficiency Transmission Grating	High Efficiency Transmission Grating
200 – 1100 nm (2048 pixels)	200 – 1100 nm (2048 pixels)	360 – 1100 nm (2048 pixels)	360 – 1100 nm (2048 pixels)
Hamamatsu S11639-01	Hamamatsu S11639-01	Hamamatsu S11639-01	Hamamatsu S11639-01
Fully Calibrated Plug-and-Play Solution	Fully Calibrated Plug-and-Play Solution	Fully Calibrated Plug-and-Play Solution	Fully Calibrated Plug-and-Play Solution
Min. Every Two Years	Min. Every Two Years	Min. Every Two Years	Min. Every Two Years

TECHNICAL SPECIFICATIONS




		BaseSpion VIS	BaseSpion UV-VIS
Standard Version			
Physical Dimensions		As standard version	
Shipping Weight		42 kg (93 lbs)	
Dimensions (L x W x H)	205-500 x 56 x 55 cm (6.7-16.4 x 2 x ft)		
Weight		38 kg (84 lbs)	
Sensor Distance Range	0.35 – 4.5 m (1.15 – 14.8 ft)		
Sensor Distance	≥ Light Source Length x 10 (Min. x 8)		
Sensor Distance Set-Up	Automatic Detector on Sensor Rail		
Light Source Diameter Range	0 - 54 cm (1.8 ft)		
Light Source (DUT) Maximum Weight	9 kg (19.8 lbs)		
Electrical Specifications		As standard version	
Power Supply Input	90 – 260 VAC, 50/60 Hz		
Power Analyzer Voltage Range	90 – 260 VAC < ±0.5 V		
Power Analyzer Current Range	0 – 3 A (Average ±0.5 mA)		
Power Analyzer Power Range @ 230 V	0 – 600 W (Average: ±0.1 W)		
Power Analyzer Power Range @ 110 V	0 – 300 W (Average: ±0.1W)		
Power Analyzer Sample Rate	70,000 Samples/sec		
Photometric Specifications			
Measurement Method	Far-Field	Far-Field	
Illuminance Range, Lux at Sensor @ 1 m	0.2 – 200,000 <±2,5% lux	0.40 – 400,000 <±2,5% lux	
Intensity Range, Min. Distance	0.0245 – 24,500 cd <±2,5% @ 0.35 m	0.050 – 29,000 cd <±2,5% @ 0.35 m	
Intensity Range, Max. Distance	4 – 4,050,000 cd <±2,5% @ 4.50 m	8 – 8,100,000 cd <±2,5% @ 4.50 m	
Flux Range, Min. Distance (Lambertian Distribution)	0.08 – 75,000 lm @ 0.35 m	Radiated spectral energy In W/nm Irradiance in µW/cm² or W/m² (all directions) 3D UV-VIS radiation field	
Flux Range, Max. Distance (Lambertian Distribution)	12.7 – 12,700,000 lm @ 4.50 m		
Flux accuracy	VIS ±4 %	VIS ±4% UVA/B ±5%, UVC ±6.5%	
Color Temperature Range	1,000 K – 10,000 K < ±35 K	1,000 K – 10,000 K < ±35 K	
Color Rendering Index	Up to 100 < ±0.7	Up to 100 < ±0.7	
Resolution, Standard	5 Degrees/Step (Auto-Detect)	5 Degrees/Step (Auto-Detect)	
Resolution, Highest	0.01 Degrees/Step (Auto-Detect)	0.01 Degrees/Step (Auto-Detect)	
Number of c-planes	2 – 72 (max. 144) automatic	2 – 72 (max. 144) automatic	
Spectrometer Type	Ibsen Photonics FREEDOM High Efficiency Transmission Grating	Ibsen Photonics FREEDOM High Efficiency Transmission Grating	
Spectrometer Range	360 - 830 nm (1024 pixels)	200 - 850 nm (2048 pixels)	
Spectrometer Detector	Hamamatsu S11639-01	Hamamatsu S11639-01	
Calibration	Fully Calibrated Plug-and-Play Solution	Fully Calibrated Plug-and-Play Solution	
Re-calibration	Min. Every Two Years	Min. Every Two Years	

BaseSpion UV-VIS-NIR	BaseSpion VIS-NIR	LightSpion	Extender for LightSpion
			
As standard version	As standard version	(Discontinued)	
		7 kg (15.4 lbs)	9 kg
		43x11.5x33.5 cm (17.1x4.5x33.5")	100 x 36 x 21 cm
		6 kg (13.2 lbs)	7 kg
		66 cm (26"), fixed	66, 115 and 182 cm
		Fixed	Fixed (Three Settings)
		-	Manual input
		0 – 8 cm (3.15") @ single-axis	0 - 22 cm
		1 kg	4 kg
As standard version	As standard version		
		90 - 260 VAC, 50/60 Hz	
		90 - 260 VAC < ±0.5 V	
		0 – 3 A (Average ±0.5 mA)	
		0 – 600 W (Average: ±0.1 W)	
		0 – 300 W (Average: ±0.1W)	
		70,000 Samples/sec	
Far-Field	Far-Field	Far-Field	
0.20 – 200,000 <±2,5% lux	0.20 – 200,000 <±2,5% lux	10 - 10,000 lux	
As UV-VIS version	As UV-VIS version	0.5 – 50,000 candela ±4% @ 66 cm	
		10 - 50,000 lm @ 66 cm (3.15")	
NIR ±4%, VIS ±4%, UVA/B ±5%, UVC ±6.5%	VIS ±4%, NIR ±4%	LED ±4%, other types ±7.8%	
1,000 K – 10,000 K < ±35 K	1,000 K – 10,000 K < ±35 K	1,000 K – 10,000 K < ±35 K	
Up to 100 < ±0.7	Up to 100 < ±0.7	Up to 100 < ±0,7	
5 Degrees/Step (Auto-Detect)	5 Degrees/Step (Auto-Detect)	7.5 Degrees/Step (Auto-Detect)	7.5 Deg./Step (Auto-Detect)
0.01 Degrees/Step (Auto-Detect)	0.01 Degrees/Step (Auto-Detect)	0.1 Degrees/Step	0.01 Degrees/Step
2 – 72 (max. 144)	2 – 72 (max. 144)	2 (standard) – 8 (manual)	2-8
Ibsen Photonics FREEDOM High Efficiency Transmission Grating	Ibsen Photonics FREEDOM High Efficiency Transmission Grating	Ibsen Photonics PEBBLE High Efficiency Transmission Grating	
200 - 1100 nm (2048 pixels)	360 - 1100 nm (2048 pixels)	360 - 830 nm (256 pixels)	
Hamamatsu S11639-01	Hamamatsu S11639-01	Hamamatsu S14739	
Fully Calibrated Plug-and-Play	Fully Calibrated Plug-and-Play	Fully Calibrated Plug and Play	
Min. Every Two Years	Min. Every Two Years	Min. Every Two Years	

AROUND THE WORLD

Viso Systems measurement solutions are being used by hundreds of customers around the world. Below are references to a few of our customers and their experience using the systems. You can read full customer reviews on www.visosystems.com/review



Matt Samuel
LEDRA Brands, USA

- The LabSpion allows us to create our own IES files, that are published on our website
- Before we outsourced ALL of our photometric testing, which was a costly and time consuming process
- We use Viso daily to assist with product development




Daniel Silverstein
Liteline, Canada

- With the LabSpion we now measure more than a dozen fixtures per week
- Colour versus angle is very helpful and a unique feature
- Reduced cost from using external labs means the system was paid back in less than 1 year



Carlton Jones
Fraen, USA

- Since 2018, LabSpion has produced hundreds of accurate measurements for us
- The LabSpion just works. Durable, easy to use, accurate, and versatile
- We can design, prototype, test, tool, mold our complex plastic lenses and reflectors better, faster and cheaper.



Martin Nähr
Stella, Brazil

- The LabSpion makes it possible to quickly compare our products for both quality control and for competitive purposes
- Fast product comparisons have improved our sales process



Daniel Mahdavi
Orluna, UK

- The LightSpion system saves us waiting 2-4 weeks for IES files from an external lab
- With our own system we can run thermal improvements, beam shape improvements, and LED selection
- R&D is faster and we are able to prototype accurately



Matthew Earnshaw
ACDC, UK

- With the LightSpion + Extender we can now turn around any measurement in few minutes
- Before we had to ship our fixtures and pay £300 per measurement
- The system was paid back in 1-2 weeks, due to quantity of measurements




Matteo Botner
Botlighting, Italy

- After developing an internal test facility, we have been much quicker and more effective in selecting materials and partners
- Customers appreciate that the company has the right instruments for R&D. This has improved our reputation in the market



Håkan Jordanson
Nokalux, Sweden

- LabSpion has reduced our measurement time significantly to an average of 8 minutes per fixture
- Before we paid €800 for a measurement at a external lab
- The quality of our lighting fixtures has increased as we can test faster



Stephan Meyer
Korona, Germany

- The use of LED technology required us to do much more measurements to maintain development schedules
- The LightSpion + Extender also made it possible for us develop solution of specialized high-end projects
- Before, it took two weeks to get a single measurement done by an external lab and would cost €650



Robert Francij
Molto Luce, Austria

- With LabSpion we are faster in the engineering phase, so we are able to bring the products to market more quickly
- We primarily use the system for measuring prototypes, i.e. efficiency of reflectors



John Cheung
Retc, Hong Kong

- BaseSpion and LabSpion allows us measure 50 lamps per week
- Viso help us to save time so we can focus on quality aspects
- The system was paid back in less than one year

Read all of the full reviews on www.visosystems.com/review

CUSTOMER SUPPORT

Installation takes less than two hours and you will be able to use your equipment from day one. As you work more with light measurements, questions will probably arise. Viso Systems take pride in assisting you as fast as possible.

GETTING FAST ANSWERS

- Call your local distributor
- Call Viso Systems’ head office
- Send us an email - info@visosystems.com
- Check the online Viso Q&A section at www.visosystems.com/q
- Check the most up-to-date manuals at www.visosystems.com/support

CONTACT

Our worldwide network of partners will be able to support you with any questions you might have. We look forward to assisting you.

HEAD OFFICE

Viso Systems (Copenhagen office)
Vesterbrogade 12, 1.
1620 Copenhagen V
Denmark

CVR: DK 29690391
Tel. +45 36991882
Mail: sales@visosystems.com

EUROPE AND MIDDLE EAST

Germany, Austria and Switzerland
Acal BFi Germany GmbH
Oppelner Straße 5
82194 Gröbenzell
Germany
Tel.: +49 (0) 8142 6520 0
Email: sales-de@acalbfi.de

United Kingdom
ACAL BFi UK Ltd.
3 The Business Centre
Molly Millars Lane, Wokingham
Berkshire RG41 2EY
United Kingdom
Tel: +44(0) 07443 815 827
Email: tom.letowski@acalbfi.co.uk

France
Acal BFi France SAS
1 allée de la Chartreuse
91080 Evry-Courcouronnes
France.Tel: +33 (0) 1 60 79 59 00
Email: sales-fr@acalbfi.fr

Netherlands, Belgium and Luxembourg
Laser 2000 Benelux C.V.
Voorbancken 13a
3645 GV Vinkeveen



The Netherlands
Tel: +31-(0)297-266191
info@laser2000.nl

Czech Republic and Slovakia
Safibra, s.r.o.
Černokostelecká 1621
251 01 Říčany
Czech Republic
Tel: + 420 323 601 615
Email: safibra@safibra.cz

Greece
Alfatec Single Member P.C
Kanari Str. 3 153 44 Gerakas
Athens
Greece
Tel: +30 2106047635, +30 2106049695
Email: sales@alfatec.gr


Turkey
TD Elektronik
Akçaburgaz Mahallesi 3080. Sokak No:5
34522 Esenyurt
İstanbul, Türkiye
Tel: +90 212 444 2733
Email: info@tdelektronik.com

EU ECODESIGN

DIRECT EXPORT TO EPREL ZIP FILES

All Viso measurement systems allow you to extract EPREL data via the Light Inspector software and the included EPREL zip file generator.

Viso software automaticly generates your zip-file – ready for upload. Pick a measurement, add a little data in the dialog window, and generate the zip-file with a single click.



AMERICAS

USA
Viso Systems HQ
Vesterbrogade 12, 1.
1620 Copenhagen V
Denmark
Email: sales@visosystems.com

USA - Local Contacts
George Dieckmann – Principal (North Am.) 770-328-8367
Tripp Roberts – Principal (Southeast) 770-331-3501
Aaron Wood – Techn. Service Manager 407-212-1210
Fatima Mercado (W-Coast, B.C + Alberta) 310-529-9358
Matt Muhr (Northeast) 610-390-0302
Tyler Tondee (Midwest Territory) 229-942-2934

Canada, Central America, South America except Argentina
Viso Systems HQ
Vesterbrogade 12, 1.
1620 Copenhagen V
Denmark
Email: sales@visosystems.com

Argentina
RGB Lighting Systems S.A.
Camarones 1562
[C1416ECD] Ciudad Autónoma de Buenos Aires
Argentina
Tel: +54 11 4581-0044
Email: info@rgbls.com

ASIA

China (Hong Kong)
MPHK Group Ltd.
Att: Peter Chan
12/F New Lee Wah Centre,
88 Tokwawan Road, Kowloon, Hong Kong
Tel: +852 2264 1500
Email: sales@mphkg.com.hk

China (Bijjing)
Titan Electro-Optics(Hong Kong)Co., Ltd. Beijing Office
Add: Room 1701-1706, The Gate Tower B, No. 19,
Zhongguancun Avenue,
Haidian District, Beijing 100080, China
Tel: +8610 6263 4840
Email: sales@teo.com.cn

China (Shanghai)
Titan Electro-Optics(Hong Kong)Co., Ltd. Shanghai
Room 0909-0916, No. 501 Wuning Road, Shanghai
200063, China
Tel: +86 21 6222 7575
Email: sales-sh@teo.com.cn

China (Shenzhen)
Titan Electro-Optics(Hong Kong)Co., Ltd. Shenzhen
Room 1106, Building B, Meilong Road,Minzhi
Street,Shenzhen,Guangdong 518131,China
Tel: +86 755 8320 5020
Email: sales-sz@teo.com.cn

India, Sri Lanka, Bangladesh, Nepal, Myanmar and Bhutan
Precision Components
Att: Mr. Rajiv Gupta
3B/8, RAMESH NAGAR, NEW DELHI
Tel: +91-11-25467625
Mob: +91-9837049353
Email: precision2001in@gmail.com

Japan
Optosirius Corporation
1-2-14, Akabane-nishi, Kita-ku
Tokyo 115-0055 Japan
Tel: +81-3-5963-6388
Email: yohei@optosirius.co.jp

Singapore, Malaysia, Indonesia, Thailand, Vietnam, Philippines and Brunei
Kenda Singapore Pte Ltd.
67 Loyang Way, Singapore 508757
Tel: +65 6543-1183 Extension 112
Email: LynnNg@Kenda.net

OCEANIA

Australia and New Zealand
LED TEKNIK GROUP Pty Ltd
Unit 9 12-20 James Court
Melbourne, Tottenham VIC 3012
Tel: +61 (0) 407 904336
Email: nick@ledtechnik.com.au
Email: noel.duncan@visosystems.com

AFRICA

South Africa
Energywise Systems Ltd
Unit 5 Edstan Business Park
2 Ibhubesi Road
Riverhorse Valley, 4017
Durban
Tel: +27 31 764-2345 / +27 87 941-0012
Email: info@energywise.co.za



WWW.VISOSYSTEMS.COM

SALES@VISOSYSTEMS.COM - TEL. +45 36991882
VISO SYSTEMS APS - COPENHAGEN - DENMARK