

SENSOR & SURVEILLANCE SYSTEMS : POSITIONERS

MERCURY POSITIONER

FIXED & MOBILE APPLICATIONS

Mercury is a dual-channel HD-SDI rugged positioner designed for both mobile and fixed applications. The positioner is intended to hold multiple balanced payloads up to 52 lb/ mobile and 75 lb/ fixed and is ideal for dual sensor EO/IR applications.



KEY FEATURES

- Extremely ruggedized, built to withstand extreme environments
- Continuous 360° rotation
- Networked IP control
- Dual channel HD-SDI pass through video channels
- Payload Weight : Fixed 75 lb (balanced)
- Payload Weight : Mobile 52 lb (balanced)
- Easy integration with Quickset's PTZ Protocol or Pelco-D

SYSTEM PERFORMANCE

Load Capacity	Mobile mounting: 52 lb balanced load stationary mounting: 75 lb balanced load
Operating Voltage Range	24 to 28 VDC, 24 VDC Nominal
Operating Current	<8.0 A peak, <6.0 A continuous (simultaneous pan & tilt movement with payloads); <2.1 A standby
Pan-Axis Range	360° continuous rotation (Dual HD-SDI slip ring)
Pan-Axis Speed	0.005°/sec to 100°/sec
Tilt-Axis Range	180° (±90°)
Tilt-Axis Speed	0.005°/sec to 100°/sec
Operating Temperature	-32° to +55 °C (-25.6° to 131°F)

Position Resolution	0.01°
Repeatability	0.05°
Motor Type/Drive	Stepper Motor/Belt Drive
Communication to Pan & Tilt	IP and Serial (RS232/422)
Control Protocol	Quickset PTZ or Pelco D
Connector Specifications	Mil-Spec 53 Conductor D38999
Load Connector Interfaces	Mil-Spec 53 Conductor D38999
Weight	52 lb (23.6 kg) base unit (no payload wings)
Test Cable and Software	6 ft test cable
Power Supply	Available upon request

MERCURY POSITIONER ACCESSORIES

Part Number	Description
CC62131	Kit, Mercury Wings and Payload Interface
CC56545	Base Cable, 53 Socket to Flying Leads (available in various lengths)
4-65741	PTU Standoff Adapter

MP 0626



© 2026 Quickset Defense Technologies, LLC. All Rights Reserved.

Product and company names listed are trademarks or trade names of their respective companies. These products are subject to export control laws and regulations of the United States government and fall under the control jurisdiction of either ITAR or EAR regulations. Please contact our company Export Representative for further information.

This document and the information hereon are property of Quickset Defense Technologies, LLC, and may be used by others only as authorized by Quickset. All rights reserved under the copyrighting laws. Specifications are subject to change, to confirm current call +1.847.498.0700.